

1 Identification of the substance/mixture and of the company/undertaking

· **Product identifier**

· **Trade name:** Resin solution X 50

· **Article number:** 1234567890

· **Application of the substance / the preparation** Raw material for resins

· **Details of the supplier of the safety data sheet**

Chemix GmbH

Chemixstraße 17

A-5020 Salzburg

Tel.: 0043/662/21 22 23

· **Information department:**

Product safety department.

Email address of the competent person: peter.mayer@chemix.com

· **Emergency telephone number:**

During normal opening times (8 am till 5:30 pm): environment protection department, Ext 123












at other times: factory fire brigade, Ext 222

2 Composition/information on ingredients

· **Chemical characterization: Mixtures**

· **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

| | | |
|------------|--|---------|
| 25068-38-6 | reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \approx 700) | 25-50% |
| |  H411;  H315; H319; H317 | |
| 108-88-3 | toluene | 10-25% |
| |  H225;  H361; H373; H304;  H315; H336 | |
| 141-78-6 | ethyl acetate | 10-25% |
| |  H225;  H319; H336 | |
| 78-92-2 | butanol | 2.5-10% |
| |  H226;  H319; H335+H336 | |
| 67-63-0 | propan-2-ol | 2.5-10% |
| |  H225;  H319; H336 | |

3 Hazards identification

· **Classification of the substance or mixture**



GHS02 Flame

H226 Flammable liquid and vapour.



GHS08 Health hazard

H361 Suspected of damaging fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

Trade name: Resin solution X 50

(Contd. of page 1)



GHS09 Environment

H411 Toxic to aquatic life with long lasting effects.



GHS07

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC**Harmful**

Harmful: danger of serious damage to health by prolonged exposure through inhalation. Possible risk of harm to the unborn child. Harmful: may cause lung damage if swallowed.

**Irritant**

Irritating to eyes and skin. May cause sensitisation by skin contact.

**Dangerous for the environment**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Flammable. Vapours may cause drowsiness and dizziness.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of international guidelines.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· Label elements**· Labelling according to EU guidelines:**

The product has been classified and marked in accordance with directives on hazardous materials.

· Code letter and hazard designation of product:**Harmful****Dangerous for the environment****· Hazard-determining components of labelling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \bar{M}_n 700)
toluene

· Risk phrases:

Flammable.

Irritating to eyes and skin.

May cause sensitisation by skin contact.

Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

(Contd. on page 3)

CA

Printing date 05/02/2011

Reviewed on 05/02/2011

Trade name: Resin solution X 50

(Contd. of page 2)

Possible risk of harm to the unborn child.
Harmful: may cause lung damage if swallowed.
Vapours may cause drowsiness and dizziness.

· Safety phrases:

Keep out of the reach of children.
Avoid contact with skin and eyes.
Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
Wear suitable gloves and eye/face protection.
If swallowed, seek medical advice immediately and show this container or label.

· Special labelling of certain preparations:

Contains epoxy constituents. See information supplied by the manufacturer.

· Hazard description:**· WHMIS-symbols:**

B2 - Flammable liquid
D2A - Very toxic material causing other toxic effects

**· Classification system:****· NFPA ratings (scale 0 - 4)**

Health = 2
Fire = 3
Reactivity = 0

· HMIS-ratings (scale 0 - 4)

Health = *2
Fire = 3
Reactivity = 0

4 First aid measures**· General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.

· After skin contact: Immediately wash with water and soap and rinse thoroughly.**· After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

CA

(Contd. on page 4)



Trade name: Resin solution X 50

(Contd. of page 3)

5 Firefighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

Trade name: Resin solution X 50

(Contd. of page 4)

· Components with limit values that require monitoring at the workplace:

| | |
|-------------------------------|---|
| 108-88-3 toluene | |
| EL | 20 ppm |
| | R |
| EV | 20 ppm |
| 141-78-6 ethyl acetate | |
| EL | 150 ppm |
| EV | 1.440 mg/m ³ , 400 ppm |
| 78-92-2 butanol | |
| EL | 100 ppm |
| EV | Short-term value: 454 mg/m ³ , 150 ppm Long-term value: 303 mg/m ³ , 100 ppm |
| 67-63-0 propan-2-ol | |
| EL | Short-term value: 400 ppm Long-term value: 200 ppm |
| EV | Short-term value: 400 ppm Long-term value: 200 ppm |

· Additional information: The lists that were valid during the creation were used as basis.

· Personal protective equipment:

· General protective and hygienic measures:

- Keep away from foodstuffs, beverages and feed.
- Immediately remove all soiled and contaminated clothing.
- Wash hands before breaks and at the end of work.
- Avoid contact with the eyes and skin.

· Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

Trade name: Resin solution X 50

(Contd. of page 5)

 · **Eye protection:**


Tightly sealed goggles

9 Physical and chemical properties

 · **General Information**

 · **Appearance:**

| | |
|---------------|------------------------------------|
| Form: | Fluid |
| Color: | According to product specification |

| | |
|----------------|----------------|
| · Odor: | Characteristic |
|----------------|----------------|

| | |
|---------------------------|-----------------|
| · Odour threshold: | Not determined. |
|---------------------------|-----------------|

| | |
|--------------------|-----------------|
| · pH-value: | Not determined. |
|--------------------|-----------------|

 · **Change in condition**

| | |
|-------------------------------------|---------------|
| Melting point/Melting range: | Undetermined. |
|-------------------------------------|---------------|

| | |
|-------------------------------------|------|
| Boiling point/Boiling range: | 77°C |
|-------------------------------------|------|

| | |
|-----------------------|------|
| · Flash point: | 26°C |
|-----------------------|------|

| | |
|---|-----------------|
| · Flammability (solid, gaseous): | Not applicable. |
|---|-----------------|

| | |
|--------------------------------|-------|
| · Ignition temperature: | 390°C |
|--------------------------------|-------|

| | |
|-------------------------------------|-----------------|
| · Decomposition temperature: | Not determined. |
|-------------------------------------|-----------------|

| | |
|-------------------------|------------------------------|
| · Auto igniting: | Product is not selfigniting. |
|-------------------------|------------------------------|

| | |
|-------------------------------|--|
| · Danger of explosion: | Product is not explosive. However, formation of explosive air/vapor mixtures are possible. |
|-------------------------------|--|

 · **Explosion limits:**

| | |
|---------------|-----------|
| Lower: | 1.2 Vol % |
|---------------|-----------|

| | |
|---------------|------------|
| Upper: | 11.5 Vol % |
|---------------|------------|

| | |
|----------------------------------|--------|
| · Vapor pressure at 20°C: | 97 hPa |
|----------------------------------|--------|

| | |
|-------------------|-----------------|
| · Density: | Not determined. |
|-------------------|-----------------|

| | |
|---------------------------|-----------------|
| · Relative density | Not determined. |
|---------------------------|-----------------|

| | |
|-------------------------|-----------------|
| · Vapour density | Not determined. |
|-------------------------|-----------------|

| | |
|---------------------------|-----------------|
| · Evaporation rate | Not determined. |
|---------------------------|-----------------|

 · **Solubility in / Miscibility with**

| | |
|---------------|-----------------------------------|
| Water: | Not miscible or difficult to mix. |
|---------------|-----------------------------------|

| | |
|---|-----------------|
| · Segregation coefficient (n-octanol/water): | Not determined. |
|---|-----------------|

 · **Viscosity:**

| | |
|-----------------|-----------------|
| Dynamic: | Not determined. |
|-----------------|-----------------|

| | |
|-------------------|-----------------|
| Kinematic: | Not determined. |
|-------------------|-----------------|

 · **Solvent content:**

| | |
|--------------------------|--------|
| Organic solvents: | 50.0 % |
|--------------------------|--------|

(Contd. on page 7)



Trade name: Resin solution X 50

(Contd. of page 6)

| | |
|--------------------------|--|
| Solids content: | 50.0 % |
| Other information | No further relevant information available. |

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**

| | | |
|-------------------------|----------|----------------------|
| 108-88-3 toluene | | |
| Oral | LD50 | 5000 mg/kg (rat) |
| Dermal | LD50 | 12124 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 5320 mg/l (mouse) |

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

12 Ecological information

- **Acquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms

CA

(Contd. on page 8)

Trade name: Resin solution X 50

(Contd. of page 7)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** *Disposal must be made according to official regulations.*

14 Transport information

· **DOT regulations:**



- **Hazard class:** 3
- **Identification number:** UN1866
- **Packing group:** III
- **Proper shipping name (technical name):** RÉSINE EN SOLUTION
- **Label:** 3

· **TDG (Transport dangerous goods):**



- **TDG class:** 3 Flammable liquids
- **Danger code (Kemler):** 30
- **UN-Number:** 1866
- **Packaging group:** III
- **Label:** 3
- **Special marking:** Symbol (fish and tree)
- **UN proper shipping name:** 1866 RESIN SOLUTION, special provision 640E, ENVIRONMENTALLY HAZARDOUS

· **Maritime transport IMDG:**



- **IMDG Class:** 3
- **UN Number:** 1866
- **Label:** 3
- **Packaging group:** III
- **EMS Number:** F-E,S-E

(Contd. on page 9)

Trade name: Resin solution X 50

(Contd. of page 8)

· **Marine pollutant:** Yes
Symbol (fish and tree)

· **Propper shipping name:** RESIN SOLUTION (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight £ 700))

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 3
· **UN/ID Number:** 1866
· **Label** 3
· **Packaging group:** III
· **Propper shipping name:** RESIN SOLUTION

· **UN "Model Regulation":** UN1866, RESIN SOLUTION, ENVIRONMENTALLY HAZARDOUS, 3, III
· **Environmental hazards:**
Product contains environmentally hazardous substances: reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight £ 700)

15 Regulatory information

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

108-88-3 toluene

78-92-2 butanol

67-63-0 propan-2-ol

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

108-88-3 toluene

(Contd. on page 10)

Trade name: Resin solution X 50

(Contd. of page 9)

· Carcinogenic categories

· EPA (Environmental Protection Agency)

| | | |
|----------|---------|----|
| 108-88-3 | toluene | II |
|----------|---------|----|

· IARC (International Agency for Research on Cancer)

| | | |
|----------|-------------|---|
| 108-88-3 | toluene | 3 |
| 67-63-0 | propan-2-ol | 3 |

· NTP (National Toxicology Program)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

| | | |
|----------|-------------|----|
| 108-88-3 | toluene | A4 |
| 67-63-0 | propan-2-ol | A4 |

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Canadian substance listings:

· Canadian Domestic Substances List (DSL)

All ingredients are listed.

· Canadian Ingredient Disclosure list (limit 0.1%)

None of the ingredients is listed.

· Canadian Ingredient Disclosure list (limit 1%)

| | |
|----------|---------------|
| 108-88-3 | toluene |
| 141-78-6 | ethyl acetate |
| 78-92-2 | butanol |
| 67-63-0 | propan-2-ol |

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard symbols:



Harmful
Dangerous for the environment

· Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \bar{M}_n 700)
toluene

· Risk phrases:

Flammable.
Irritating to eyes and skin.
May cause sensitisation by skin contact.
Harmful: danger of serious damage to health by prolonged exposure through inhalation.
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Possible risk of harm to the unborn child.

(Contd. on page 11)

Trade name: Resin solution X 50

(Contd. of page 10)

*Harmful: may cause lung damage if swallowed.
Vapours may cause drowsiness and dizziness.*

· Safety phrases:

Keep out of the reach of children.

Avoid contact with skin and eyes.

Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.

Wear suitable gloves and eye/face protection.

If swallowed, seek medical advice immediately and show this container or label.

· Special labeling of certain preparations:

Contains epoxy constituents. See information supplied by the manufacturer.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Abbreviations and acronyms:

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

WHMIS: Workplace Hazardous Materials Information System (Canada)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent